



Window Care Set

Productinformation Article no. 2408

24.03.2015

The Kreidezeit Window Care Set is for the maintenance of wooden frame windows treated with Kreidezeit Stand Oil Paint or coloured Wood Lazures.

To maintain the protective coat of the surface and its fresh look regular maintenance and care is recommended. Minimal effort needed as renovation coatings are not required for a long time because of the durability of the paint after treatment.

■ Full declaration of ingredients

Care Soap: Olive oil soap. Care Oil: linseed oil, linseed stand oil, tung stand oil, lead-free drying agents.

■ Inspection

Treated surfaces should be visually checked every six months for dirt and damage; treat and clean if necessary.

During the half-yearly inspection & cleaning the gloss of coated surfaces must be assessed. Areas that have lost their brilliance must be immediately treated with the Kreidezeit Window Care Set. All areas with a sufficient brilliance should NOT be treated, because too frequent usage on still glossy surfaces can lead to a sticky and greasy looking surface.

Kreidezeit Stand Oil Paints and Wood Lazures are environmentally friendly and therefore deliberately contain no fungicides. Even conventional wood coating systems equipped with fungicides commonly show mould (blackening, deep shadows). It is important to check for fungus (usually small black dots on the surface) regularly at least every six months. Wipe off the mould with water and Kreidezeit Care Soap.

Because the coated weather bars are the most exposed to the weather, their condition should also be checked every six months.

■ Cleaning

Don't clean the wooden windows right after installation. Paint and silicon need approximately 4 weeks to dry completely. Please clean the metal weather bar after installation. The drainage slots must not be clogged.

Dirt can be rinsed off with a soft sponge and Care Soap (1 table-spoon soap mixed in 1 litre of water). Excessive dirt can be treated with a more concentrated soap solution.

■ Cleaning and Care

As a rule of thumb, maintenance is necessary on sunny or windward sides once a year and on lee sides every 2 years. However, due to weather conditions and exposure these intervals could vary significantly. In principle there are no definite maintenance intervals for the Kreidezeit Stand Oil Paint or Wood Lazure system.

Let cleaned surfaces dry completely. Wipe the surfaces that have lost their gloss, especially on sunny or windward sides,

gently with a cloth soaked in Care Oil. Wipe off any residue after 10 - 15 minutes with a dry cloth (residue oil can get sticky and very shiny!). The colour intensity will return. The application and drying temperature should be at least 10°C (50°F) over a period of at least 48 hours.

■ Repainting

Repainting is necessary in the following situations: Stand Oil Paints in the exterior are strongly weathered, the colour has faded away, the wooden surface is visible, the pigments have washed out from the rain. The surface has to be cleaned with Care Soap and still glossy parts should be sanded slightly (120-150 grain).

For renovation on Kreidezeit Wood Lazures should be repainted with Wood Lazure interior/ exterior (Prod.No. 320) tinted with Kreidezeit pigments up to 175 gram pigment per 1 litre Wood Lazure or with coloured Wood Lazure (Prod.No. 480-488). For renovation Kreidezeit Stand Oil Paints should be repainted with Stand Oil Paints -top Coating- (Prod.No. D 1600-1612). The weather bars on the sunny sides should be repainted at least every 2 years.

■ Storage

When closed air tight and stored in a frost-protected area the Kreidezeit Care Oil and Care Soap have a shelf life of at least 2 years.

■ Disposal of product residue

Please do not allow product residue to reach the sewer system, but keep it sealed air tight to use up on a later occasion. Dried out product residue can be disposed of in household waste. Completely emptied containers can be recycled. Please follow the official regulations for waste disposal of paint residue in your area.

■ Coverage

100 ml Care Oil covers up to 5 m² of treated surface.

■ Package size

	Content	Reach Care Oil
Art. 2408	100 ml Care Oli	5 m ²
	100 ml Care Soap	

■ Hazard Classification

Labelling is unnecessary; there are no hazardous materials.

■ Labelling according to ChemVOCFarbV

Maximum VOC emissions: (Kat. A/f): 700 g/l (2010), product contains a maximum of 3 g/l VOC.



Window Care Set

Productinformation Article no. 2408

24.03.2015

■ Safety Notes

Attention: Due to the content of natural vegetable oil there is the danger of spontaneous combustion. It means that, if the product has not fully dried, all cleaning cloths, sponges, grinding dust, polishing pads etc. have to be stored in an air-tight metal container or in water. Make also sure that no oil is touching porous insulation materials while painting for the same reason (danger of spontaneous combustion). The product itself is not self-combustible. **Keep out of reach of children.** Pay attention to possible allergies against natural ingredients. Product will yellow. Due to the natural ingredients used in the product a certain smell will occur!

The statements above are compiled from our own experience and latest technological developments. Due to difference in usage and different environmental influences as to the usage on variable textures and surfaces of materials legal liability cannot be warranted for each of the statements above. The user is obliged to test the product before use with regard to its suitability for the intended area of applications (apply a coating on a test area).

As soon as a new edition of this information sheet with new revision status is published or the product is changed, the previous statements will become invalid. The latest product information can be retrieved from Kreidezeit directly or from our website: www.kreidezeit.de