

For processing, the current product information is to be observed, available at: www.kreidezeit.de/en

Substrate	Surface preparation / priming	Intermediate coat / final coat
<ul style="list-style-type: none"> › Formerly wallpapered walls › Mixed substrates <i>old plasters with Repairs, Filling places, Cable slots, structural differences</i> 	<ol style="list-style-type: none"> 1. repair small damaged areas with Wall Filler 2. Fleece-Wallpaper or ingrain wallpaper <p>or</p> <ol style="list-style-type: none"> 1. Thoroughly wash off old wallpaper paste 2. Casein Primer or Vega Primer 3. fill the entire surface with Wall Filler, Lime Wall Finish -smooth-, Lime Wall Finish -fine- or Lime Wall Finish -medium- 4. optionally: treat penetrating stains with Alum Priming Salt 5. Casein Primer or Vega Primer 	<ul style="list-style-type: none"> › Vega Wallpaint › Clay Paint -smooth- or -textured- › Lime Paint -smooth- or -textured- › Lime Paint -high texture- › Casein Marble Paint › Brush- and Roll-on Plaster › Distemper, glue-bound › Full-tone Paint
<ul style="list-style-type: none"> › Emulsion paints <i>except natural resin dispersion</i> <p><i>absorbent</i></p> <p><i>Test coating required!</i></p>	<ul style="list-style-type: none"> › Casein Primer or Vega Primer 	<ul style="list-style-type: none"> › Vega Wallpaint › Clay Paint -smooth- or -textured- › Lime Paint -smooth- or -textured- › Lime Paint -high texture- › Casein Marble Paint › Brush- and Roll-on Plaster › GekkkoSOL Paints › Distemper, glue-bound › Full-tone Paint
<ul style="list-style-type: none"> › Gypsum- and lime-gypsum plaster › Gypsum fillers › lime, lime-cement and cement plasters, › sand-lime bricks › concrete › absorbent bricks › clay plaster <p><i>new/ untreated</i></p> <p><i>Pay particular attention to formwork oil residues in concrete! (wetting test / remove if necessary)</i></p>	<ul style="list-style-type: none"> › Casein Primer or Vega Primer › Paint Glue for Distemper 	<ul style="list-style-type: none"> › Vega Wallpaint › Clay Paint -smooth- or -textured- › Lime Paint -smooth- or -textured- › Lime Paint -high texture- › Casein Marble Paint › Brush- and Roll-on Plaster › GekkkoSOL Paints (not on clay plaster) › Distemper, glue-bound › Full-tone Paint

For processing, the current product information is to be observed, available at: www.kreidezeit.de/en

Substrate	Surface preparation / priming	Intermediate coat / final coat
<ul style="list-style-type: none"> > Ingrain wallpaper > Paper wallpaper > Fleece Wallpaper <p><i>untreated</i></p>	<ul style="list-style-type: none"> > none 	<ul style="list-style-type: none"> > Vega Wallpaint > Clay Paint -smooth- or -textured- > Lime Paint -smooth- or -textured- > Lime Paint -high texture- > Casein Marble Paint > Brush- and Roll-on Plaster > GekkkoSOL Paints > Distemper, glue-bound > Full-tone Paint
<ul style="list-style-type: none"> > plastic wallpapers > Vinyl foam wallpapers 	<ul style="list-style-type: none"> > remove wallpaper and replace with Fleece Wallpaper or ingrain wallpaper (no subsequent priming required) 	<ul style="list-style-type: none"> > Vega Wallpaint > Clay Paint -smooth- or -textured- > Lime Paint -smooth- or -textured- > Lime Paint -high texture- > Casein Marble Paint > Brush- and Roll-on Plaster > GekkkoSOL Paints > Distemper, glue-bound > Full-tone Paint
<ul style="list-style-type: none"> > Plasterboard > Gypsum fibreboards <p><i>without reinforcement strips</i></p> <p><i>untreated or formerly wallpapered, Q1-Q4</i></p>	<ul style="list-style-type: none"> > Fleece Wallpaper or ingrain wallpaper (no subsequent priming required) 	<ul style="list-style-type: none"> > Vega Wallpaint > Clay Paint -smooth- or -textured- > Lime Paint -smooth- or -textured- > Lime Paint -high texture- > Casein Marble Paint > Brush- and Roll-on Plaster > GekkkoSOL Paints > Distemper, glue-bound > Full-tone Paint
<ul style="list-style-type: none"> > Plasterboard > Gypsum fibreboards <p><i>with reinforcement strips</i></p> <p><i>untreated,</i> <i>Q2, only joint-filled</i></p>	<ol style="list-style-type: none"> 1. Wall Filler (entirely) 2. apply Casein Primer or Vega Primer 	<ul style="list-style-type: none"> > Vega Wallpaint > Clay Paint -smooth- or -textured- > Lime Paint -smooth- or -textured- > Lime Paint -high texture- > Casein Marble Paint > Brush- and Roll-on Plaster > Distemper, glue-bound > Full-tone Paint
<ul style="list-style-type: none"> > Plasterboard > Gypsum fibreboards <p><i>with reinforcement strips</i></p> <p><i>untreated,</i> <i>Q3-Q4, filled over the entire surface</i></p>	<ul style="list-style-type: none"> > Casein Primer or Vega Primer > Paint Glue for Distemper 	<p><i>for Q3, only white coatings are recommended, Q4 also pigmented</i></p> <ul style="list-style-type: none"> > Vega Wallpaint > Clay Paint -smooth- or -textured- > Lime Paint -smooth- or -textured- > Lime Paint -high texture- > Casein Marble Paint > Brush- and Roll-on Plaster > GekkkoSOL FINE-Grain > Distemper, glue-bound > Full-tone Paint

For processing, the current product information is to be observed, available at: www.kreidezeit.de/en

Substrate	Surface preparation / priming	Intermediate coat / final coat
<ul style="list-style-type: none"> > Latex paints > Emulsion paints <i>except natural resin dispersion</i> > Tiles, Oil based coats <p><i>non-absorbent</i></p>	<ol style="list-style-type: none"> 1. Grind shiny surfaces 2. clean, de-grease, dedust 	<ul style="list-style-type: none"> > GekkkoSOL Paints
	<ol style="list-style-type: none"> 1. Grind shiny surfaces 2. clean, de-grease, dedust 3. GekkkoSOL FINE-Grain 	<ul style="list-style-type: none"> > Vega Wallpaint > Clay Paint -smooth- or -textured- > Lime Paint -smooth- or -textured- > Brush- and Roll-on Plaster > Distemper, glue-bound > Full-tone Paint
<ul style="list-style-type: none"> > OSB, chipboards > Wood-based materials 	<ol style="list-style-type: none"> 1. joint filling and reinforcement according to manufacturer's instructions 2. Fleece Wallpaper 	<ul style="list-style-type: none"> > Vega Wallpaint > Clay Paint -smooth- or -textured- > Lime Paint -smooth- or -textured- > Lime Paint -high texture- > Casein Marble Paint > Brush- and Roll-on Plaster > GekkkoSOL Paints > Distemper, glue-bound > Full-tone Paint
<ul style="list-style-type: none"> > aerated concrete > Calcium silicate boards > porous lightweight bricks 	<p><i>Not suitable for direct painting.</i></p> <ol style="list-style-type: none"> 1. Special plaster for aerated concrete or calcium silicate, 2. apply Casein Primer or Vega Primer 	<ul style="list-style-type: none"> > Vega Wallpaint > Clay Paint -smooth- or -textured- > Lime Paint -smooth- or -textured- > Lime Paint -high texture- > Casein Marble Paint > Brush- and Roll-on Plaster > GekkkoSOL Paints > Distemper, glue-bound > Full-tone Paint
	<ol style="list-style-type: none"> 1. Casein Primer or Vega Primer 2. apply 2 coats Lime Wall Finish -medium- „wet-on-wet“, 3. apply Casein Primer or Vega Primer again 	
<ul style="list-style-type: none"> > Soft fibre boards 	<ol style="list-style-type: none"> 1. Base plaster coating according to manufacturer's specifications with reinforcement 2. Casein Primer or Vega Primer 	<ul style="list-style-type: none"> > Vega Wallpaint > Clay Paint -smooth- or -textured- > Lime Paint -smooth- or -textured- > Lime Paint -high texture- > Casein Marble Paint > Brush- and Roll-on Plaster > GekkkoSOL Paints > Distemper, glue-bound > Full-tone Paint

For tinting, please refer to the colour charts and colour fans "Wall paints & plasters". Wallpaper glue residues must be thoroughly washed off on all surfaces from which wallpaper was previously removed. Otherwise subsequent coats may flake off or old wallpaper glue may show through in colour.