

Page 1 of 16
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 22.02.2023 / 0001
Replacing version dated / version: 22.02.2023 / 0001
Valid from: 22.02.2023
PDF print date: 22.02.2023
Lime Wall Finish -fine- (Kalk Haftputz -fein-)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Lime Wall Finish -fine- (Kalk Haftputz -fein-)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

mortar, rendering

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

KREIDEZEIT Naturfarben GmbH
Kassemühle 3
31195 Lamspringe
Tel.: +49 (0) 506 0 608 06 50
Fax: +49 (0) 506 0 608 06 80
E-Mail: info@kreidezeit.de
Homepage: www.kreidezeit.de

Distributor:
Mike Wye & Associates Ltd
Buckland Filleigh Sawmills
Shebbear
Beaworthy
EX21 5RN
Tel: +44 1409 281644
Email: sales@mikewye.co.uk

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

+49 551 19240 (D-37075 Göttingen, 24 hour)

Telephone number of the company in case of emergencies:

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
--------------	-----------------	------------------

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 22.02.2023 / 0001
Replacing version dated / version: 22.02.2023 / 0001
Valid from: 22.02.2023
PDF print date: 22.02.2023
Lime Wall Finish -fine- (Kalk Haftputz -fein-)

STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Eye Dam.	1	H318-Causes serious eye damage.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H335-May cause respiratory irritation. H315-Causes skin irritation. H318-Causes serious eye damage.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.
P261-Avoid breathing dust. P271-Use only outdoors or in a well-ventilated area. P280-Wear protective gloves / eye protection / face protection.
P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor.
P405-Store locked up.
P501-Dispose of contents / container to an approved waste disposal facility.

Calcium dihydroxide

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Calcium dihydroxide	Substance for which an EU exposure limit value applies.
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	215-137-3
CAS	1305-62-0
content %	10-<25

Page 3 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0001
 Replacing version dated / version: 22.02.2023 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Lime Wall Finish -fine- (Kalk Haftputz -fein-)

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors

Skin Irrit. 2, H315
 Eye Dam. 1, H318
 STOT SE 3, H335

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
 Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Protect uninjured eye.

Follow-up examination by an ophthalmologist.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

coughing

eyes, reddened

watering eyes

irritation of the eyes

reddening of the skin

Dermatitis (skin inflammation)

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire.

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.
Ensure sufficient ventilation, remove sources of ignition.
Avoid dust formation with solid or powder products.
Leave the danger zone if possible, use existing emergency plans if necessary.
Keep unprotected persons away.
Avoid contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent surface and ground-water infiltration, as well as ground penetration.
Prevent from entering drainage system.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
Avoid build up of dust.
Avoid contact with eyes or skin.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
Store product closed and only in original packing.
Not to be stored in gangways or stair wells.
Store at room temperature.
Store in a dry place.

7.3 Specific end use(s)

No information available at present.
Observe the instructions for good working practice and the recommendations for risk assessment.

Page 5 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0001
 Replacing version dated / version: 22.02.2023 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Lime Wall Finish -fine- (Kalk Haftputz -fein-)

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries,
 depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name			Calcium dihydroxide
WEL-TWA:	1 mg/m ³ (9) (WEL, EU)	WEL-STEL:	4 mg/m ³ (9) (WEL, EU) ---
Monitoring procedures:		ISO 15202 (Workplace air - Determination of metals and metalloids in airborne particulate matter by Inductively Coupled Plasma Atomic Emission Spectrometry), Part 1-3 - 2012(Part 1), 2012(Part 2), 2004 (Part 3) - NIOSH 7020 (CALCIUM and compounds, as Ca) - 1994 OSHA ID-121 (Metal and metalloid particulates in workplace atmospheres (Atomic absorption)) - 2002 - EU project BC/CEN/ENTR/000/2002-16 card 42-4 (2004) - OSHA PV2121 (Gravimetric Determination) - 2003	
BMGV: ---		Other information: ---	
Chemical Name			Quartz
WEL-TWA:	0,1 mg/m ³ (silica, respirable, crystalline)	WEL-STEL:	--- ---
Monitoring procedures:		INSHT MTA/MA-036/A00 (Determination of Quartz in Air – Membrane Filter Method/ Xray Diffraction) - 2000, 2004 MDHS 101/2 (Crystalline silica in respirable airborne dust – Direct on-filter analysis by infrared spectroscopy and X-ray diffraction) - 2015 - EU project BC/CEN/ENTR/000/2002-16 card 52-1 (2004) NIOSH 7500 (Crystalline Silica, by XRD (filter redeposition)) - 2003 - EU project BC/CEN/ENTR/000/2002-16 card 52-6 (2004) - NIOSH 7601 (SILICA, CRYSTALLINE, by VIS) - 2003 - NIOSH 7602 (Crystalline Silica, by IR (KBr pellet)) - 2003 - NIOSH 7603 (QUARTZ in coal mine dust, by IR (redeposition)) - 2017 - OSHA ID-142 (Quartz and Cristobalite in Workplace Atmospheres) - 2016	
BMGV: ---		Other information: ---	
Chemical Name			Calcium carbonate
WEL-TWA:	4 mg/m ³ (respirable dust), 10 mg/m ³ (total inhalable dust)	WEL-STEL:	--- ---
Monitoring procedures:		---	
BMGV: ---		Other information: ---	
Chemical Name			Starch
WEL-TWA:	10 mg/m ³ (total inhalable dust), 4 mg/m ³ (respirable dust)	WEL-STEL:	--- ---
Monitoring procedures:		---	
BMGV: ---		Other information: ---	
Chemical Name			general dust limit
WEL-TWA:	10 mg/m ³ (inhal. dust), 4 mg/m ³ (respir. dust)	WEL-STEL:	--- ---
Monitoring procedures:		---	
BMGV: ---		Other information: ---	

Calcium dihydroxide

Page 6 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0001
 Replacing version dated / version: 22.02.2023 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Lime Wall Finish -fine- (Kalk Haftputz -fein-)

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,49	mg/l	
	Environment - soil		PNEC	1080	mg/kg dw	
	Environment - marine		PNEC	0,32	mg/l	
	Environment - sewage treatment plant		PNEC	3	mg/l	
	Environment - sporadic (intermittent) release		DMEL	0,49	mg/l	
Consumer	Human - inhalation	Short term, local effects	DNEL	4	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	1	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	4	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	1	mg/m3	

96 WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Chemical resistant protective gloves (EN ISO 374).

Page 7 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0001
 Replacing version dated / version: 22.02.2023 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Lime Wall Finish -fine- (Kalk Haftputz -fein-)

If applicable
 Protective gloves made of butyl (EN ISO 374).
 Protective Neoprene® / polychloroprene gloves (EN ISO 374).
 Protective nitrile gloves (EN ISO 374).
 Minimum layer thickness in mm:
 0,5
 Permeation time (penetration time) in minutes:
 480
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.
 Protective hand cream recommended.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 If OES or MEL is exceeded.
 If applicable, filter P2 (EN 143), code colour white
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Solid, powder
Colour:	White
Odour:	Odourless
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Not combustible.
Lower explosion limit:	Does not apply to solids.
Upper explosion limit:	Does not apply to solids.
Flash point:	Does not apply to solids.
Auto-ignition temperature:	Does not apply to solids.
Decomposition temperature:	There is no information available on this parameter.
pH:	~12,5
Kinematic viscosity:	There is no information available on this parameter.
Solubility:	Mixable
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	There is no information available on this parameter.
Relative vapour density:	Does not apply to solids.
Particle characteristics:	There is no information available on this parameter.

9.2 Other information

Explosives:

Product is not explosive.

Oxidizing solids:

No

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Moisture

10.5 Incompatible materials

Avoid contact with strong acids.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Kalk Haftputz -fein-						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Calcium dihydroxide						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure)	
Acute toxicity, by dermal route:	LD50	>2500	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	

Page 9 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0001
 Replacing version dated / version: 22.02.2023 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Lime Wall Finish -fine- (Kalk Haftputz -fein-)

Skin corrosion/irritation:					OECD 431 (In Vitro Skin Corrosion - Human Skin Model Test)	Non-caustic
Skin corrosion/irritation:				Rabbit		Irritant, in vivo
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						breathing difficulties, abdominal pain, drowsiness, thirst, fever, sore throat, cornea opacity, coughing, headaches, mucous membrane irritation, fatigue

Quartz						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Symptoms:						respiratory distress, coughing, mucous membrane irritation

Calcium carbonate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	
Acute toxicity, by oral route:	LD50	> 5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant

Page 10 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0001
 Replacing version dated / version: 22.02.2023 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Lime Wall Finish -fine- (Kalk Haftputz -fein-)

Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Mechanical irritation possible.
Respiratory or skin sensitisation:						No (skin contact)
Germ cell mutagenicity:					in vitro	Negative
Carcinogenicity:						Negative, administered as Ca-lactate
Reproductive toxicity:						Negative, administered as Ca-carbonate

Starch						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg			

11.2. Information on other hazards

Kalk Haftputz -fein-						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Kalk Haftputz -fein-							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.

Calcium dihydroxide

Page 11 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0001
 Replacing version dated / version: 22.02.2023 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Lime Wall Finish -fine- (Kalk Haftputz -fein-)

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	160	mg/l	Gambusia affinis	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LC50	96h	457	mg/l			marine water
12.1. Toxicity to fish:	LC50	96h	50,6	mg/l			freshwater
12.1. Toxicity to daphnia:	NOEC/NOEL	14d	32	mg/l			marine water
12.1. Toxicity to daphnia:	LC50	96h	158	mg/l			marine water
12.1. Toxicity to daphnia:	EC50	48h	49,1	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	184,57	mg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	48	mg/l			freshwater
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							Not relevant for inorganic substances.
12.4. Mobility in soil:							Calcium dihydroxide, which is sparingly soluble, presents a low mobility in most soils.
12.5. Results of PBT and vPvB assessment							Not relevant for inorganic substances.
12.6. Endocrine disrupting properties:							Not to be expected
12.7. Other adverse effects:							pH-value of > 12 will rapidly decrease as result of dilution and carbonation., Even though this product can be used to neutralise over-acidified water, when 1g/l is exceeded organisms in the water may be affected adversely.

Page 12 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0001
 Replacing version dated / version: 22.02.2023 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Lime Wall Finish -fine- (Kalk Haftputz -fein-)

Toxicity to bacteria:							In high concentrations the product provokes an increase in temperature and of the pH-value. It is used to sanitise sewage sludge
Other organisms:	NOEC/NOEL		2000	mg/kg dw			soil macroorganisms
Other organisms:	NOEC/NOEL		12000	mg/kg dw			soil microorganisms
Other organisms:	NOEC/NOEL	21d	1080	mg/kg			terrestrial plants

Quartz							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							Low
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Calcium carbonate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to annelids:					Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	Negative
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.6. Endocrine disrupting properties:							Not to be expected
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna		

Page 13 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0001
 Replacing version dated / version: 22.02.2023 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Lime Wall Finish -fine- (Kalk Haftputz -fein-)

12.1. Toxicity to algae:	EC50	72h	>200	mg/l	Desmodesmus subspicatus		
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Inorganic products cannot be eliminated from water through biological purification methods.
12.3. Bioaccumulative potential:							Not relevant for inorganic substances.
12.4. Mobility in soil:							Not relevant for inorganic substances.
12.5. Results of PBT and vPvB assessment							Not relevant for inorganic substances.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

10 13 99 wastes not otherwise specified

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Untampered packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	Not applicable
14.2. UN proper shipping name:	
Not applicable	
14.3. Transport hazard class(es):	Not applicable
14.4. Packing group:	Not applicable
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	Not applicable

Page 14 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0001
 Replacing version dated / version: 22.02.2023 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Lime Wall Finish -fine- (Kalk Haftputz -fein-)

Classification code: Not applicable
 LQ: Not applicable
 Transport category: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 0 %

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: n.a.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Skin Irrit. — Skin irritation

Eye Dam. — Serious eye damage

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EpCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

Page 16 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0001
 Replacing version dated / version: 22.02.2023 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Lime Wall Finish -fine- (Kalk Haftputz -fein-)

IUPAC International Union for Pure Applied Chemistry
 LC50 Lethal Concentration to 50 % of a test population
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 NIOSH National Institute for Occupational Safety and Health (USA)
 NLP No-longer-Polymer
 NOEC, NOEL No Observed Effect Concentration/Level
 OECD Organisation for Economic Co-operation and Development
 org. organic
 OSHA Occupational Safety and Health Administration (USA)
 PBT persistent, bioaccumulative and toxic
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 ppm parts per million
 PVC Polyvinylchloride
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
 SVHC Substances of Very High Concern
 Tel. Telephone
 TOC Total organic carbon
 UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
 VOC Volatile organic compounds
 vPvB very persistent and very bioaccumulative
 wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
 No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.