

Page 1 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 22.02.2023 / 0002
Replacing version dated / version: 15.02.2022 / 0001
Valid from: 22.02.2023
PDF print date: 22.02.2023
Shellac Sealing Primer

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Shellac Sealing Primer

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Coating

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

KREIDEZEIT Naturfarben GmbH
Kassemühle 3
31195 Lamspringe
Tel.: +49 (0) 506 0 608 06 50
Fax: +49 (0) 506 0 608 06 80
E-Mail: info@kreidezeit.de
Homepage: www.kreidezeit.de

Distributor:

Mike Wye & Associates Ltd
Buckland Filleigh Sawmills
Shebbear
Beaworthy
EX21 5RN
Tel: +44 1409 281644
Email: sales@mikewye.co.uk

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

+49 551 19240 (D-37075 Göttingen, 24 hour)

Telephone number of the company in case of emergencies:

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

| Hazard class | Hazard category | Hazard statement |
|--------------|-----------------|------------------|
|--------------|-----------------|------------------|

Flam. Liq. 2 H225-Highly flammable liquid and vapour.

2.2 Label elements
Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H225-Highly flammable liquid and vapour.

P102-Keep out of reach of children.
 P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233-Keep container tightly closed.
 P501-Dispose of contents / container to an approved waste disposal facility.

EUH211-Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
 The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).
 Dangerous vapours heavier than air.
 In case of spreading near the ground, flashback to distance sources of ignition is possible.

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

| | |
|---|--|
| Ethanol | |
| Registration number (REACH) | 01-2119457610-43-XXXX |
| Index | 603-002-00-5 |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 200-578-6 |
| CAS | 64-17-5 |
| content % | 25-<50 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Flam. Liq. 2, H225 Eye Irrit. 2, H319 |
| Specific Concentration Limits and ATE | Eye Irrit. 2, H319: >=50 % |

| | |
|--|--|
| Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm) | |
|--|--|

Page 3 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0002
 Replacing version dated / version: 15.02.2022 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Shellac Sealing Primer

| | |
|---|-------------------------------|
| Registration number (REACH) | --- |
| Index | 022-006-002 |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 236-675-5 |
| CAS | 13463-67-7 |
| content % | 10-<25 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Carc. 2, H351 (as inhalation) |

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
 Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
 Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
 In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Nausea
 dizziness
 vomiting

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2
 Extinction powder
 Water jet spray
 Alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon
 Metal oxides

Page 4 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 22.02.2023 / 0002
Replacing version dated / version: 15.02.2022 / 0001
Valid from: 22.02.2023
PDF print date: 22.02.2023
Shellac Sealing Primer

Toxic gases
Possible build up of explosive/highly flammable vapour/air mixture.

5.3 Advice for firefighters

For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.
Ensure sufficient ventilation, remove sources of ignition.
Avoid dust formation with solid or powder products.
Leave the danger zone if possible, use existing emergency plans if necessary.
Keep unprotected persons away.
Avoid contact with eyes or skin.
If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent surface and ground-water infiltration, as well as ground penetration.
Prevent from entering drainage system.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.
Fill the absorbed material into lockable containers.
Flush residue using copious water.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
Avoid inhalation of the vapours.
Avoid contact with eyes or skin.
Keep away from sources of ignition - Do not smoke.
Take measures against electrostatic charging, if appropriate.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.

GB

Page 5 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0002
 Replacing version dated / version: 15.02.2022 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Shellac Sealing Primer

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Store product closed and only in original packing.
 Not to be stored in gangways or stair wells.
 Observe special storage conditions.
 Do not store with flammable or self-igniting materials.
 Protect from direct sunlight and warming.
 Store in a well-ventilated place.
 Store cool.

7.3 Specific end use(s)

No information available at present.
 Observe the instructions for good working practice and the recommendations for risk assessment.
 Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries,
 depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| Chemical Name | Ethanol | |
|---|--|-----|
| WEL-TWA: 1000 ppm (1920 mg/m ³) | WEL-STEL: --- | --- |
| Monitoring procedures: | <ul style="list-style-type: none"> - Draeger - Alcohol 25/a Ethanol (81 01 631) - Compur - KITA-104 SA (549 210) - DFG (D) (Lösungsmittelgemische), Methode Nr. 6 DFG (E) (Solvent mixtures) - 2013, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004) - DFG Meth. Nr. 2 (D) (Lösungsmittelgemische) - 2013 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004) - DFG Meth. Nr. 3 (D) (Lösungsmittelgemische) - 2013 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004) | |
| BMGV: --- | Other information: --- | |
| Chemical Name | Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm) | |
| WEL-TWA: 10 mg/m ³ (total inhalable dust), 4 mg/m ³ (respirable dust) | WEL-STEL: --- | --- |
| Monitoring procedures: | --- | |
| BMGV: --- | Other information: --- | |
| Chemical Name | Quartz | |
| WEL-TWA: 0,1 mg/m ³ (silica, respirable, crystalline) | WEL-STEL: --- | --- |
| Monitoring procedures: | <ul style="list-style-type: none"> - INSHT MTA/MA-036/A00 (Determination of Quartz in Air – Membrane Filter Method/ Xray Diffraction) - 2000, 2004 - MDHS 101/2 (Crystalline silica in respirable airborne dust – Direct on-filter analysis by infrared spectroscopy and X-ray diffraction) - 2015 - EU project BC/CEN/ENTR/000/2002-16 card 52-1 (2004) - NIOSH 7500 (Crystalline Silica, by XRD (filter redeposition)) - 2003 - EU project BC/CEN/ENTR/000/2002-16 card 52-6 (2004) - NIOSH 7601 (SILICA, CRYSTALLINE, by VIS) - 2003 - NIOSH 7602 (Crystalline Silica, by IR (KBr pellet)) - 2003 - NIOSH 7603 (QUARTZ in coal mine dust, by IR (redeposition)) - 2017 - OSHA ID-142 (Quartz and Cristobalite in Workplace Atmospheres) - 2016 | |
| BMGV: --- | Other information: --- | |
| Chemical Name | Silicon dioxide | |

GB

Page 6 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0002
 Replacing version dated / version: 15.02.2022 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Shellac Sealing Primer

| | | |
|--|---------------|-----|
| WEL-TWA: 6 mg/m ³ (total inh. dust), 2,4 mg/m ³ (resp. dust) | WEL-STEL: --- | --- |
|--|---------------|-----|

| | |
|----------------------------|------------------------|
| Monitoring procedures: --- | Other information: --- |
| BMGV: --- | |

| Chemical Name | Talc |
|---------------|------|
|---------------|------|

| | | |
|--|---------------|-----|
| WEL-TWA: 1 mg/m ³ (res. dust) | WEL-STEL: --- | --- |
|--|---------------|-----|

| | |
|----------------------------|------------------------|
| Monitoring procedures: --- | Other information: --- |
| BMGV: --- | |

| Chemical Name | Potassium mica |
|---------------|----------------|
|---------------|----------------|

| | | |
|--|---------------|-----|
| WEL-TWA: 0,8 mg/m ³ (respirable dust), 10 mg/m ³ (total inhalable dust) (Mica) | WEL-STEL: --- | --- |
|--|---------------|-----|

| | |
|----------------------------|------------------------|
| Monitoring procedures: --- | Other information: --- |
| BMGV: --- | |

| Ethanol | | | | | | |
|---------------------|--|-----------------------------|------------|-------|-------------------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - freshwater | | PNEC | 0,96 | mg/l | |
| | Environment - marine | | PNEC | 0,79 | mg/l | |
| | Environment - water, sporadic (intermittent) release | | PNEC | 2,75 | mg/l | |
| | Environment - sewage treatment plant | | PNEC | 580 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 3,6 | mg/kg dry weight | |
| | Environment - soil | | PNEC | 0,63 | mg/kg dry weight | |
| | Environment - oral (animal feed) | | PNEC | 0,38 | g/kg feed | |
| | Environment - sediment, marine | | PNEC | 2,9 | mg/kg dry weight | |
| Consumer | Human - dermal | Short term, local effects | DNEL | 950 | mg/m ³ | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 114 | mg/m ³ | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 87 | mg/kg | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 206 | mg/kg bw/d | |
| Consumer | Human - inhalation | Short term, local effects | DNEL | 950 | mg/m ³ | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 343 | mg/kg bw/d | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 950 | mg/m ³ | |
| Workers / employees | Human - inhalation | Short term, local effects | DNEL | 1900 | mg/m ³ | |

| Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm) | | | | | | |
|---|--|------------------|------------|-------|------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |

| | | | | | | |
|--|--|--|--|--|--|--|
| | | | | | | |
|--|--|--|--|--|--|--|

Page 7 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0002
 Replacing version dated / version: 15.02.2022 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Shellac Sealing Primer

| | | | | | | |
|---------------------|--|-----------------------------|------|--------|------------|--|
| | Environment - freshwater | | PNEC | 0,184 | mg/l | |
| | Environment - marine | | PNEC | 0,0184 | mg/l | |
| | Environment - water, sporadic (intermittent) release | | PNEC | 0,193 | mg/l | |
| | Environment - sewage treatment plant | | PNEC | 100 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 1000 | mg/kg dw | |
| | Environment - sediment, marine | | PNEC | 100 | mg/kg dw | |
| | Environment - soil | | PNEC | 100 | mg/kg dw | |
| | Environment - oral (animal feed) | | PNEC | 1667 | mg/kg feed | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 700 | mg/kg bw/d | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 10 | mg/m3 | |

| Silicon dioxide | | | | | | |
|---------------------|--|--------------------------|------------|-------|------------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - oral (animal feed) | | PNEC | 60000 | mg/kg feed | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 4 | mg/m3 | |

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

Page 8 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 22.02.2023 / 0002
Replacing version dated / version: 15.02.2022 / 0001
Valid from: 22.02.2023
PDF print date: 22.02.2023
Shellac Sealing Primer

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
Chemical resistant protective gloves (EN ISO 374).
If applicable
Protective gloves in butyl rubber (EN ISO 374).
Protective gloves made of fluorocarbon rubber (EN ISO 374).
Protective Neoprene® / polychloroprene gloves (EN ISO 374).
Protective nitrile gloves (EN ISO 374).
Minimum layer thickness in mm:

0,5
Permeation time (penetration time) in minutes:
480
Protective hand cream recommended.
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
If OES or MEL is exceeded.
Gas mask filter A (EN 14387), code colour brown
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
Not applicable

Additional information on hand protection - No tests have been performed.
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
Selection of materials derived from glove manufacturer's indications.
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|---|--|
| Physical state: | Liquid |
| Colour: | White |
| Odour: | Characteristic, Alcoholic |
| Melting point/freezing point: | There is no information available on this parameter. |
| Boiling point or initial boiling point and boiling range: | 78-81 °C (Ethanol) |
| Flammability: | Flammable |
| Lower explosion limit: | There is no information available on this parameter. |
| Upper explosion limit: | There is no information available on this parameter. |

Page 9 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0002
 Replacing version dated / version: 15.02.2022 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Shellac Sealing Primer

| | |
|--|--|
| Flash point: | 12-21 °C (Ethanol) |
| Auto-ignition temperature: | There is no information available on this parameter. |
| Decomposition temperature: | There is no information available on this parameter. |
| pH: | 4-5 (10 %) |
| Kinematic viscosity: | There is no information available on this parameter. |
| Solubility: | partially |
| Partition coefficient n-octanol/water (log value): | Does not apply to mixtures. |
| Vapour pressure: | There is no information available on this parameter. |
| Density and/or relative density: | ~1,40 g/cm ³ |
| Relative vapour density: | There is no information available on this parameter. |
| Particle characteristics: | Does not apply to liquids. |

9.2 Other information

| | |
|--------------------|---|
| Explosives: | Product is not explosive. When using: development of explosive vapour/air mixture possible. |
| Oxidising liquids: | No |

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

| Shellac Sealing Primer | | | | | | |
|---|----------|-------|------|----------|-------------|--------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | | | | | | n.d.a. |
| Acute toxicity, by dermal route: | | | | | | n.d.a. |
| Acute toxicity, by inhalation: | | | | | | n.d.a. |
| Skin corrosion/irritation: | | | | | | n.d.a. |
| Serious eye damage/irritation: | | | | | | n.d.a. |
| Respiratory or skin sensitisation: | | | | | | n.d.a. |
| Germ cell mutagenicity: | | | | | | n.d.a. |
| Carcinogenicity: | | | | | | n.d.a. |
| Reproductive toxicity: | | | | | | n.d.a. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | n.d.a. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | n.d.a. |

Page 10 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0002
 Replacing version dated / version: 15.02.2022 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Shellac Sealing Primer

| | | | | | | |
|--------------------|--|--|--|--|--|--------|
| Aspiration hazard: | | | | | | n.d.a. |
| Symptoms: | | | | | | n.d.a. |

| Ethanol | | | | | | |
|---|----------|----------|------------|------------------------|--|-------------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | 10470 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >2000 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | 51-124,7 | mg/l/4h | Rat | OECD 403 (Acute Inhalation Toxicity) | Vapours |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Eye Irrit. 2 |
| Respiratory or skin sensitisation: | | | | Mouse | OECD 429 (Skin Sensitisation - Local Lymph Node Assay) | No (skin contact) |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | Mouse | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test) | Negative |
| Carcinogenicity: | NOAEL | >3000 | mg/kg | Rat | OECD 451 (Carcinogenicity Studies) | 24 mon |
| Reproductive toxicity: | NOAEL | 5200 | mg/kg bw/d | Rat | OECD 416 (Two-generation Reproduction Toxicity Study) | |
| Specific target organ toxicity - repeated exposure (STOT-RE): | NOAL | >20 | mg/l | Rat | OECD 403 (Acute Inhalation Toxicity) | Male |
| Specific target organ toxicity - repeated exposure (STOT-RE): | NOAEL | 1730 | mg/kg/d | Rat | OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) | Female |

Page 11 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0002
 Replacing version dated / version: 15.02.2022 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Shellac Sealing Primer

| | | | | | | |
|-----------|--|--|--|--|--|---|
| Symptoms: | | | | | | respiratory distress, drowsiness, unconsciousness, drop in blood pressure, vomiting, coughing, headaches, intoxication, drowsiness, mucous membrane irritation, dizziness, nausea |
|-----------|--|--|--|--|--|---|

| Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$) | | | | | | |
|--|----------|-------|---------|------------------------|--|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure) | |
| Acute toxicity, by dermal route: | LD50 | >5000 | mg/kg | Rabbit | | |
| Acute toxicity, by inhalation: | LC50 | >6,8 | mg/l/4h | Rat | | |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant, Mechanical irritation possible. |
| Respiratory or skin sensitisation: | | | | Mouse | OECD 429 (Skin Sensitisation - Local Lymph Node Assay) | Not sensitising |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | No (skin contact) |
| Germ cell mutagenicity: | | | | Mouse | OECD 474 (Mammalian Erythrocyte Micronucleus Test) | Negative |
| Germ cell mutagenicity: | | | | Mammalian | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | (Ames-Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Reproductive toxicity (Developmental toxicity): | | | | Rat | OECD 414 (Prenatal Developmental Toxicity Study) | No indications of such an effect. |

Page 12 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0002
 Replacing version dated / version: 15.02.2022 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Shellac Sealing Primer

| | | | | | | |
|---|-------|------|---------|-----|--|---|
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | Not irritant (respiratory tract). (90d) |
| Specific target organ toxicity - repeated exposure (STOT-RE), oral: | NOAEL | 3500 | mg/kg/d | Rat | | (90d) |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEC | 10 | mg/m3 | Rat | | (90d) |
| Symptoms: | | | | | | mucous membrane irritation, coughing, respiratory distress, drying of the skin. |

| Quartz | | | | | | |
|-------------------|----------|-------|------|----------|-------------|--|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Symptoms: | | | | | | respiratory distress, coughing, mucous membrane irritation |

| Silicon dioxide | | | | | | |
|---|----------|--------|---------|------------|--------------------------------|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | Analogous conclusion |
| Acute toxicity, by dermal route: | LD50 | >5000 | mg/kg | Rabbit | | References |
| Acute toxicity, by inhalation: | LC50 | >0,139 | mg/l/4h | Rat | | References, Maximum achievable concentration. |
| Skin corrosion/irritation: | | | | Rabbit | | Not irritant, References |
| Serious eye damage/irritation: | | | | Rabbit | | Not irritant, Mechanical irritation possible., References |
| Respiratory or skin sensitisation: | | | | Guinea pig | | Not sensitising |
| Germ cell mutagenicity: | | | | | | Negative |
| Carcinogenicity: | | | | | | No indications of such an effect. |
| Reproductive toxicity (Developmental toxicity): | | | | | | No indications of such an effect. |
| Symptoms: | | | | | | eyes, reddened |

| Talc | | | | | | |
|--------------------------------|----------|-------|-------|----------|-------------|-------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | | |

Page 13 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0002
 Replacing version dated / version: 15.02.2022 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Shellac Sealing Primer

| | | | | | | |
|------------------------------------|------|-------|-------|--------|--|----------------------------|
| Acute toxicity, by dermal route: | LD50 | >2000 | mg/kg | Rat | | |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |
| Skin corrosion/irritation: | | | | | | Not irritant |
| Respiratory or skin sensitisation: | | | | | | Not sensitising |
| Germ cell mutagenicity: | | | | | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Carcinogenicity: | | | | | | Negative |
| Reproductive toxicity: | | | | Rat | | Negative |
| Symptoms: | | | | | | mucous membrane irritation |

11.2. Information on other hazards

| Shellac Sealing Primer | | | | | | |
|----------------------------------|----------|-------|------|----------|-------------|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Endocrine disrupting properties: | | | | | | Does not apply to mixtures. |
| Other information: | | | | | | No other relevant information available on adverse effects on health. |

| Ethanol | | | | | | |
|--------------------|----------|-------|------|----------|-------------|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Other information: | | | | | | Excessive alcohol consumption during pregnancy induces the foetus alcohol syndrome (reduced weight at birth, physical and mental disorders)., There is no sign that this syndrome is also caused by dermal or inhalative absorption., Experiences on persons. |

SECTION 12: Ecological information

Page 14 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0002
 Replacing version dated / version: 15.02.2022 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Shellac Sealing Primer

Possibly more information on environmental effects, see Section 2.1 (classification).

Shellac Sealing Primer

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|--|----------|------|-------|------|----------|-------------|---|
| 12.1. Toxicity to fish: | | | | | | | n.d.a. |
| 12.1. Toxicity to daphnia: | | | | | | | n.d.a. |
| 12.1. Toxicity to algae: | | | | | | | n.d.a. |
| 12.2. Persistence and degradability: | | | | | | | n.d.a. |
| 12.3. Bioaccumulative potential: | | | | | | | n.d.a. |
| 12.4. Mobility in soil: | | | | | | | n.d.a. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | n.d.a. |
| 12.6. Endocrine disrupting properties: | | | | | | | Does not apply to mixtures. |
| 12.7. Other adverse effects: | | | | | | | No information available on other adverse effects on the environment. |

Ethanol

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|--------------------------------------|-----------|------|-------------------|------|---------------------|--|---|
| 12.1. Toxicity to fish: | LC50 | 96h | 13000 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to fish: | NOEC/NOEL | 120h | 250 | mg/l | Brachydanio rerio | OECD 212 (Fish, Short-term Toxicity Test on Embryo and Sac-fry Stages) | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | 5414 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | 10d | 9,6 | mg/l | Ceriodaphnia spec. | | References |
| 12.1. Toxicity to algae: | EC50 | 72h | 275 | mg/l | Chlorella vulgaris | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | 28d | 97 | % | activated sludge | OECD 301 B (Ready Biodegradability - Co2 Evolution Test) | Readily biodegradable |
| 12.3. Bioaccumulative potential: | Log Pow | | (-0,35) - (-0,32) | | | | Bioaccumulation is unlikely (LogPow < 1). |
| 12.3. Bioaccumulative potential: | BCF | | 0,66 - 3,2 | | | | |
| 12.4. Mobility in soil: | H (Henry) | | 0,000138 | | | | |
| 12.4. Mobility in soil: | Koc | | 1,0 | | | | Highestimated |

Page 15 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0002
 Replacing version dated / version: 15.02.2022 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Shellac Sealing Primer

| | | | | | | | |
|--|-----------|----|-------|------|------------------|--|-------------------------------------|
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| Toxicity to bacteria: | IC50 | 3h | >1000 | mg/l | activated sludge | OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation)) | Analogous conclusion |
| Other organisms: | NOEC/NOEL | | 280 | mg/l | Lemna gibba | OECD 201 (Alga, Growth Inhibition Test) | |
| Other information: | COD | | 1,9 | g/g | | | |
| Other information: | BOD5 | | 1 | g/g | | | |

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|--|-----------|------|--------|-------|---------------------------------|--|--|
| 12.1. Toxicity to fish: | LC50 | 96h | >100 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | LC50 | 48h | >100 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | EC50 | 72h | 16 | mg/l | Pseudokirchneriella subcapitata | U.S. EPA-600/9-78-018 | |
| 12.2. Persistence and degradability: | | | | | | | Not relevant for inorganic substances. |
| 12.3. Bioaccumulative potential: | BCF | 42d | 9,6 | | | | Not to be expected |
| 12.3. Bioaccumulative potential: | BCF | 14d | 19-352 | | | | Oncorhynchus mykiss |
| 12.4. Mobility in soil: | | | | | | | Negative |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| Toxicity to bacteria: | | | >5000 | mg/l | Escherichia coli | | |
| Toxicity to bacteria: | LC0 | 24h | >10000 | mg/l | Pseudomonas fluorescens | | |
| Toxicity to annelids: | NOEC/NOEL | | >1000 | mg/kg | Eisenia foetida | | |
| Water solubility: | | | | | | | Insoluble20°C |

Quartz

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|--------------------------------------|----------|------|-------|------|----------|-------------|--|
| 12.2. Persistence and degradability: | | | | | | | Not relevant for inorganic substances. |
| 12.3. Bioaccumulative potential: | | | | | | | Not to be expected |
| 12.4. Mobility in soil: | | | | | | | Low |

Page 16 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0002
 Replacing version dated / version: 15.02.2022 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Shellac Sealing Primer

| | | | | | | | |
|--|--|--|--|--|--|--|-------------------------------------|
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
|--|--|--|--|--|--|--|-------------------------------------|

| Silicon dioxide | | | | | | | |
|--|----------|------|--------|------|-------------------|--|-------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | >10000 | mg/l | Brachydanio rerio | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | EC50 | 24h | >10000 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | EL50 | 72h | >10000 | mg/l | | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | | | | | | Abiotically degradable. |
| 12.3. Bioaccumulative potential: | | | | | | | Not to be expected |
| 12.4. Mobility in soil: | | | | | | | Not to be expected |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

| Talc | | | | | | | |
|--|----------|------|-------|------|-------------------|-------------|--|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| Water solubility: | | | <0,1 | % | | | |
| 12.1. Toxicity to fish: | LC50 | 96h | 100 | g/l | Brachydanio rerio | | |
| 12.2. Persistence and degradability: | | | | | | | Not relevant for inorganic substances. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 01 11 waste paint and varnish containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Page 17 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0002
 Replacing version dated / version: 15.02.2022 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Shellac Sealing Primer

Uncontaminated packaging can be recycled.
 Dispose of packaging that cannot be cleaned in the same manner as the substance.
 Do not perforate, cut up or weld uncleaned container.
 Residues may present a risk of explosion.

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

| | |
|-----------------------------------|----------------|
| 14.1. UN number or ID number: | 1263 |
| 14.2. UN proper shipping name: | |
| UN 1263 PAINT | |
| 14.3. Transport hazard class(es): | 3 |
| 14.4. Packing group: | II |
| 14.5. Environmental hazards: | Not applicable |
| Tunnel restriction code: | D/E |
| Classification code: | F1 |
| LQ: | 5 L |
| Transport category: | 2 |



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

| Hazard categories | Notes to Annex I | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements |
|-------------------|------------------|---|---|
| P5c | | 5000 | 50000 |

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): ~ 35 %

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0002
 Replacing version dated / version: 15.02.2022 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Shellac Sealing Primer

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2, 3, 7, 9, 14, 15
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

| Classification in accordance with regulation (EC) No. 1272/2008 (CLP) | Evaluation method used |
|---|------------------------------------|
| Flam. Liq. 2, H225 | Classification based on test data. |

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.
 H351 Suspected of causing cancer by inhalation.
 H319 Causes serious eye irritation.

Flam. Liq. — Flammable liquid
 Eye Irrit. — Eye irritation
 Carc. — Carcinogenicity

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
 Guidelines for the preparation of safety data sheets as amended (ECHA).
 Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
 Safety data sheets for the constituent substances.
 ECHA Homepage - Information about chemicals.
 GESTIS Substance Database (Germany).
 German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
 EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
 National Lists of Occupational Exposure Limits for each country as amended.
 Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 ATE Acute Toxicity Estimate
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor

Page 19 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2023 / 0002
 Replacing version dated / version: 15.02.2022 / 0001
 Valid from: 22.02.2023
 PDF print date: 22.02.2023
 Shellac Sealing Primer

BSEF The International Bromine Council
 bw body weight
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
 EC European Community
 ECHA European Chemicals Agency
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
 etc. et cetera
 EU European Union
 EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 Koc Adsorption coefficient of organic carbon in the soil
 Kow octanol-water partition coefficient
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC (Code) International Bulk Chemical (Code)
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 IUPAC International Union for Pure Applied Chemistry
 LC50 Lethal Concentration to 50 % of a test population
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 NIOSH National Institute for Occupational Safety and Health (USA)
 NLP No-longer-Polymer
 NOEC, NOEL No Observed Effect Concentration/Level
 OECD Organisation for Economic Co-operation and Development
 org. organic
 OSHA Occupational Safety and Health Administration (USA)
 PBT persistent, bioaccumulative and toxic
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 ppm parts per million
 PVC Polyvinylchloride

Page 20 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 22.02.2023 / 0002
Replacing version dated / version: 15.02.2022 / 0001
Valid from: 22.02.2023
PDF print date: 22.02.2023
Shellac Sealing Primer

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.