

# **Alcohol**

Product information article no. 4303

09.01.2024

#### Naturfarben

### **■** General

Kreidezeit Alcohol (ethyl alcohol, spirit) is a fermentation alcohol. It is obtained by fermenting plant material containing sugar or starch through certain yeasts (analogous to beer/wine production) and subsequent distillation. Distillation tax is levied on pure alcohol as a beverage. For tax reasons, so-called denaturants are therefore added to it for technical applications, which make it inedible or cause immediate vomiting if swallowed.

## **■** Usage

For diluting alcohol dissolved Kreidezeit products such as Shellac Sealing Primer. For cleaning tools that have been soiled with these products.

For stain removal and degreasing of surfaces. For dissolving alcohol-soluble natural resins such as shellac and copal.

#### **■** Composition

Ethyl alcohol (96 %), isopropanol, Bitrex, methyl ethyl ketone

#### **■** Container Sizes

| Article no. 4303-500 | 500 ml |
|----------------------|--------|
| Article no. 4303-1   | 1 l    |
| Article no. 4303-2.5 | 2,5 l  |
| Article no. 4303-5   | 5 l    |
|                      |        |

For prices, please refer to the valid price list.

#### **■ Storage**

Shelf life approx. 2 years if unopened. Always keep opened containers hermetically closed.

# **■** Warning

Pay attention to possible natural substance allergies. The natural raw materials used produce a typical product smell! **Keep out of reach of children.** 

# **■ Disposing Leftover Product**

Do not discharge product residues into the waste water, but keep them airtightly sealed and use them later. Put completely emptied containers into the collection of recyclables. The current official regulations for the disposal of paint and paint residues must be observed.



#### ■ Hazard statements

- H 225: Highly flammable liquid and vapour.
- H 319: Causes serious eye irritation.

# **■** Precautionary statements

- P 210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P 240: Ground/bond container and receiving equipment.
- P 241: Use explosion-proof electrical/ventilating/lighting/equipment.
- P 243: Take precautionary measures against static discharge.
- P 280: Wear protective gloves/protective clothing/eye protection/face protection.
- P 303+P 361+P 353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P 305+P 351+P 338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P 337+P 313: If eye irritation persists: Get medical advice/attention.

The information above was determined based on our most recent experiences. Due to processing methods and environmental influences, as well as the varying nature of the substrates, liability for the general validity of the individual recommendations is excluded. Users must test the product prior to application to ensure it is fit for the designated purpose (sample coating).

This document is no longer valid if a new version is published or the product is modified. The latest product information is available at Kreidezeit directly or on the Internet: www.kreidezeit.de