

Naturfarben GmbH

# **Balsamic turpentine**

Productinformation Article no. 446-448

14.12.2017

## **■** General

Balsamic turpentine is extracted by steam distillation from the resin outflow (balsam) of various pine species. As a rule, about 70% of the pine balsam consists of rosin resin and 30% turpentine oil. The world's pine forests release several million tons of turpentine oil to the atmosphere every year.

The earth has been used to it for millions of years and can handle it without damaging the atmosphere.

Balsamic Turpentine is a clear and low-viscosity essential oil with a peculiar, penetrating fresh smell and a bitterly pungent taste. Approximately 300,000 tons are produced annually. It is the most important essential oil in terms of quantity. The main producers are the USA, with about half of the world's production. Also the countries of the former USSR, Scandinavia, China, Portugal, Spain.

### **■** Uses

For diluting oil-based Kreidezeit products: Wood Lazure, Standoil Paint, Hard Oils, Multi Purpose Wax, and natural oils such as: Linseed Oil Varnish, Linseed Standoil and Tung Standoil. For cleaning tools that have been soiled with these products. For stain removal and degreasing of surfaces. For dissolving terpene-soluble natural resins such as rosin, dammar.

## **■** Composition

Balsamic turpentine, double rectified

#### **■** Container Sizes

For prices, please refer to the valid price list.

#### **■ Storage**

Shelf life approx. 2 years if unopened. Always keep opened containers hermetically closed.

## **■** Warning

Pay attention to possible natural substance allergies. The natural raw materials used produce a typical product smell! Keep out of reach of children.

# ■ Disposing Leftover Product

Do not discharge product residues into the waste water, but keep them airtightly sealed and use them later. Put completely emptied containers into the collection of recyclables. The current official regulations for the disposal of paint and paint residues must be observed.







#### ■ Hazard statements

- H 226: Flammable liquid and vapour.
- H 302: Harmful if swallowed.
- H 304: May be fatal if swallowed and enters airways.
- H 312: Harmful in contact with skin.
- H 315: Causes skin irritation.
- H 319: Causes serious eye irritation.
- H 332: Harmful if inhaled.
- H 411: Toxic to aquatic life with long lasting effects.
- EUH 208: Contains balsamic turpentine. May produce an allergic reaction.

## ■ Precautionary statements

- P 261: Avoid breathing dust / fume / gas / mist / vapours/spray.
- P 280: Wear protective gloves/protective clothing/eye protection/face protection.
- P 301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.
- P 303+361+353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P 305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P 312: Call a POISON CENTER/doctor if you feel unwell.
- P 331: Do NOT induce vomiting.
- P 333+313: If skin irritation or rash occurs: Get medical advice/attention.
- P 405: Store locked up.
- P 501: Dispose of contents/container to waste disposal.

The information above was determined based on our most recent experiences. Due to application methods and environmental influences, as well as the varying nature of the substrates, liability for the general validity of the individual recommendations is excluded. Users must test the product prior to application to ensure it is fit for the designated purpose (sample coating).

This document is no longer valid if a new version is published or the product is modified. For the latest product information, please contact Kreidezeit directly or visit our website at www.kreidezeit.de