KREIDEZEIT

Naturfarben

Siccative

Productinformation Article no. 8108 10.08.2018

■ Uses

Kreidezeit Siccative is used as an additive to oil paints and oil glazes to accelerate the drying of natural drying oils.
Also suitable for the re-siccativation of old oil paints which have lost their drying power over long storage periods.

Kreidezeit Siccative is not an autonomous coating and must not be used as such, e.g. for application to sticky oiled surfaces for their subsequent hardening.

■ Properties

very economical, cobalt-, lead- and barium-free, vegan

■ Composition (Full Declaration)

lead-free drying agent (manganese-fatty acid compound), white spirit

■ Preliminary tests / Competence

The handling of drying agents requires good expertise and usually requires preliminary tests with smaller amounts of material. We will be happy to advise you in case of need.

■ Application

- **Siccativation of natural drying oils**
  max. 1 % siccative on the oil content (i.e. 10ml siccative on 1 liter e.g. linseed oil or safflower oil).
  Stir the siccative thoroughly into the oil and leave to rest for 24 hours before processing.

- **Re-siccativation of old oil paints**
  max. 0.5 % siccative (i.e. 5 ml to 1 litre old oil paint or oil glaze)
  Stir in the siccative thoroughly and leave to rest for 24 hours before processing.

Do not exceed the stated additional quantities, as overdosing can lead to strong and irreversible tackiness of the coatings.

■ Cleaning The Tools

Immediately after use with Balsamic Turpentine (art. 4301).

■ Container Sizes

Article no. 8108-50 50 ml
Article no. 8108-250 250 ml
Please refer to the valid price list for prices.

■ Storage

Stored in a cool, dark, frost-free place and airtight sealed, shelf life at least 2 years.

■ Disposing Leftover Product

Do not pour product residues into waste water. Dispose of product residues via local pollutant collection points.

■ Warning

Wear gloves while working with Siccative. Avoid skin contact. Wash hands thoroughly after work. In case of skin contact, wash thoroughly with soap and water. Store out of reach of children.

Danger

■ Hazard Statements

- H315: Causes skin irritation.

■ Precautionary Statements

- P264: wash thoroughly after handling
- P280: Wear protective gloves.
- P302 + P352 IF ON SKIN: Wash with plenty of water.
- P332 + P313 If skin irritation occurs: Get medical advice/ attention.
- P362 + P364: Take off contaminated clothing and wash it before reuse.

The information above was determined based on our most recent experiences. Due to processing methods and environmental influences, as well as the varying nature of the substrates, liability for the general validity of the individual recommendations is excluded. Users must test the product prior to application to ensure it is fit for the designated purpose (sample coating).

This document is no longer valid if a new version is published or the product is modified. For the latest product information, please contact Kreidezeit directly or visit our website at www.kreidezeit.de

Kreidezeit Naturfarben GmbH Kassemuehle 3 . D-31195 Lamspringe . Phone +49 50 60 - 60 80 30
Fax +49 50 60 - 60 80 680 . info@kreidezeit.de . www.kreidezeit.de